estpassportQ&A



Bessere Qualität , bessere Dienstleistungen!

We offer free update service for one year Http://www.testpassport.ch

Exam : JN0-280

Title : Data Center, Associate

(JNCIA-DC)

Version: DEMO

- 1. Which of the following is an important consideration when configuring BFD?
- A. Setting a very high multiplier to avoid false positives
- B. Using the same BFD interval on all devices in the network
- C. Adjusting the BFD interval and multiplier according to network needs
- D. Disabling all other failure detection mechanisms

Answer: C

- 2.In the context of Layer 2 switching, what does RSTP stand for?
- A. Rapid Spanning Tree Protocol
- B. Routing Switch Transport Protocol
- C. Redundant Switching Tree Protocol
- D. Resilient Switching Transport Protocol

Answer: A

- 3. What is the default route preference for a static route on a Junos device?
- A. 130
- B. 15
- C. 10
- D. 5

Answer: D

- 4. Which statement is correct about a five-stage IP fabric topology?
- A. There is a maximum of five hops between any end-devices
- B. They are commonly referred to as interconnected data centers
- C. There is a maximum of three hops between any end-devices
- D. They are typically deployed in small to medium data centers

Answer: A

- 5. What is the primary purpose of using aggregate routes in a network?
- A. To dynamically adjust to network changes
- B. To summarize and reduce the number of routes in the routing table
- C. To filter unwanted traffic
- D. To statically define a route to a specific destination

Answer: B